

DEF Suction Connection

<p><b>Multi-Use (aka Reusable), 55 Gallon Drum Suction Connection</b></p>	<p><b>Multi-Use (aka Reusable), 275 Gallon Tote Suction Connection</b></p>	<p><b>Multi-Use (aka Reusable), 330 Gallon Tote Suction Connection</b></p>
<p><i>Required Components</i>  <b>Dispense Coupler</b> (outlet to pump)  <ul style="list-style-type: none"> <li>• <b>DEF-34A</b> (Stainless; 3/4" hose barb outlet) or</li> <li>• <b>DEF-34PL</b> (Composite; 3/4" hose barb outlet) or</li> <li>• <b>DEF-54</b> (Stainless; Vapor recovery capability)</li> </ul> <b>Container Valve</b> (2" Buttress (M), barbed inlet)  <ul style="list-style-type: none"> <li>• <b>DEF-40A</b> (Stainless) or</li> <li>• <b>DEF-40PL</b> (Composite)</li> </ul> <b>Downtube</b>  <ul style="list-style-type: none"> <li>• <b>DEF-TUBE55</b> (Composite, cut to length)</li> </ul> <p><i>Optional Components</i></p> <p>Tool</p> <ul style="list-style-type: none"> <li>• <b>DEF-41</b> (Container valve install/remove)</li> </ul> </p>	<p><i>Required Components</i>  <b>Dispense Coupler</b> (outlet to pump)  <ul style="list-style-type: none"> <li>• <b>DEF-34A</b> (Stainless; 3/4" hose barb outlet) or</li> <li>• <b>DEF-34PL</b> (Composite; 3/4" hose barb outlet) or</li> <li>• <b>DEF-54</b> (Stainless; Vapor recovery capability)</li> </ul> <b>Container Valve</b> (2" Buttress (M), barbed inlet)  <ul style="list-style-type: none"> <li>• <b>DEF-40A</b> (Stainless) or</li> <li>• <b>DEF-40PL</b> (Composite)</li> </ul> <b>Downtube</b>  <ul style="list-style-type: none"> <li>• <b>DEF-TUBE55</b> (Composite, cut to length)</li> </ul> <p><i>Optional Components</i></p> <p>Tool</p> <ul style="list-style-type: none"> <li>• <b>DEF-41</b> (Container valve install/remove)</li> </ul> <p>Cap</p> <ul style="list-style-type: none"> <li>• <b>DEF-69</b> (Comp., 6" Buttress (F), 2" Buttress (F))</li> </ul> </p>	<p><i>Required Components</i>  <b>Dispense Coupler</b> (outlet to pump)  <ul style="list-style-type: none"> <li>• <b>DEF-34A</b> (Stainless; 3/4" hose barb outlet) or</li> <li>• <b>DEF-34PL</b> (Composite; 3/4" hose barb outlet) or</li> <li>• <b>DEF-54</b> (Stainless; Vapor recovery capability)</li> </ul> <b>Container Valve</b> (2" Buttress (M), barbed inlet)  <ul style="list-style-type: none"> <li>• <b>DEF-40A</b> (Stainless) or</li> <li>• <b>DEF-40PL</b> (Composite)</li> </ul> <b>Downtube</b>  <ul style="list-style-type: none"> <li>• <b>DEF-TUBE55</b> (Composite, cut to length)</li> </ul> <p><i>Optional Components</i></p> <p>Tool</p> <ul style="list-style-type: none"> <li>• <b>DEF-41</b> (Container valve install/remove)</li> </ul> <p>Cap</p> <ul style="list-style-type: none"> <li>• <b>DEF-69</b> (Comp., 6" Buttress (F), 2" Buttress (F))</li> </ul> </p>
<p><b>Single-Use (aka Disposable), 55 Gallon Drum Suction Connection</b></p>	<p><b>Single-Use (aka Disposable), 275 Gallon Tote Suction Connection</b></p>	<p><b>Single-Use (aka Disposable), 330 Gallon Tote Suction Connection</b></p>
<p><i>Required Components</i>  <b>Dispense Coupler</b> (3/4" hose barb outlet to pump)  <ul style="list-style-type: none"> <li>• <b>DEF-39</b> (Stainless)</li> </ul> <b>Container Valve</b> (2" Buttress (M), barbed inlet)  <ul style="list-style-type: none"> <li>• <b>DEF-42</b> (Composite)</li> </ul> <b>Downtube</b>  <ul style="list-style-type: none"> <li>• <b>DEF-43</b> (Composite)</li> </ul> <p><i>Optional Components</i></p> <p>Tool</p> <ul style="list-style-type: none"> <li>• <b>DEF-73</b> (Container valve install/remove)</li> </ul> </p>	<p><i>Required Components</i>  <b>Dispense Coupler</b> (3/4" hose barb outlet to pump)  <ul style="list-style-type: none"> <li>• <b>DEF-39</b> (Stainless)</li> </ul> <b>Container Valve</b> (2" Buttress (M), barbed inlet)  <ul style="list-style-type: none"> <li>• <b>DEF-42</b> (Composite)</li> </ul> <b>Downtube</b>  <ul style="list-style-type: none"> <li>• <b>DEF-44</b> (Composite)</li> </ul> <p><i>Optional Components</i></p> <p>Tool</p> <ul style="list-style-type: none"> <li>• <b>DEF-73</b> (Container valve install/remove)</li> </ul> <p>Cap</p> <ul style="list-style-type: none"> <li>• <b>DEF-69</b> (Comp., 6" Buttress (F), 2" Buttress (F))</li> </ul> </p>	<p><i>Required Components</i>  <b>Dispense Coupler</b> (3/4" hose barb outlet to pump)  <ul style="list-style-type: none"> <li>• <b>DEF-39</b> (Stainless)</li> </ul> <b>Container Valve</b> (2" Buttress (M), barbed inlet)  <ul style="list-style-type: none"> <li>• <b>DEF-42</b> (Composite)</li> </ul> <b>Downtube</b>  <ul style="list-style-type: none"> <li>• <b>DEF-45</b> (Composite)</li> </ul> <p><i>Optional Components</i></p> <p>Tool</p> <ul style="list-style-type: none"> <li>• <b>DEF-73</b> (Container valve install/remove)</li> </ul> <p>Cap</p> <ul style="list-style-type: none"> <li>• <b>DEF-69</b> (Comp., 6" Buttress (F), 2" Buttress (F))</li> </ul> </p>

NOTE: Multi-use and single-use components are physically incompatible with one another; you cannot mix and match parts between the two systems.  
NOTE: Stainless Steel and Composite components are compatible with one another within the Multi-Use system. The same is true for the Single-Use system.  
NOTE: Physical positioning/connection: 1) Dispense Coupler outlet connects to pump suction hose, twist-lock into Container Valve, 2) Container Valve is intermediate between the Dispense Coupler and the Downtube, 3) Downtube outlet connects to the Container Valve inlet, downtube inlet is inserted into DEF drum/tote.