

Data Sheet, 635X Series Non-Metered Control Valves

- **WORKING PRESSURE:**
 - 0 PSI minimum
 - 635193: 600 PSI maximum
 - 635395-2: 900 PSI maximum
 - 635392: 1,000 PSI maximum
- **SHIPPING:**
 - One box
 - *Weight:* 4 pounds
 - *Dimensions:* 6" x 6" x 24"
 - *Included:* Manual (1x), filter (1x)
 - *NOTE:* 635392 does include swivel, does *not* include trigger lock
 - *NOTE:* 635193 does *not* include swivel (accessory), does include trigger lock
 - *NOTE:* 635395-2 does *not* include swivel (accessory), does *not* include trigger lock
- **COMPATIBILITY:**
 - Antifreeze Mixtures
 - Automatic Transmission Fluid
 - Gear Oil
 - Hydraulic Oil
 - Motor Oil
 - Synthetic Oil
- **WORKING FLOW RATE:**
 - 635392: 3 GPM maximum
 - 635193 & 635395-2: 10 GPM maximum
- **THREADS:**
 - *Swivel:* 635192 @ 1/2"-14 NPT (F). *NOTE:* Sealant required
 - *Handle Inlet:* 635193 & 635395-2 @ 3/4" NPTF (F). American Dryseal Pipe Threads
- **WARRANTY (*Defects in material and workmanship, non-wear parts*):**
 - Five years from date of purchase
- **ACCESSORIES:**
 - PR-750 pressure relief kit (thermal expansion protection)
 - Swivel guards for the 635392 valve (rubber; various colors available)
 - Swivel, Hi-Flow, 635108 (3/4" NPTF, M x F) for use on 635193 & 635395-2 valves
- **INSTALLATION RECOMMENDATIONS:**
 - *Plumbing:* 1/2" or 3/4" diameter. Keep plumbing, etc. away from heat sources
 - *Sealant:* Teflon tape topped with petroleum compatible pipe dope (e.g., Gasoil)



635X
(Handle, Swivel, Tip Extension
determine item number)