

Data Sheet, TIM-3108-100P Hose Reel (Platinum Series Premium Double-Arm)

Low Pressure (300 PSI), powder-coated, double-arm reel,
1/2" x 100' delivery hose

- HOSE:
 - Working pressure, 300 PSI maximum
- SHIPPING:
 - One box
 - Weight: 95 pounds
 - Dimensions: 9.25" x 25.5" x 23"
- COMPATIBILITY:
 - Air
 - Water
- MAXIMUM MOUNTING HEIGHT:
 - 14' above floor
- MOUNTING BASE HOLE PATTERN:
 - 7" x 8"
 - Four holes for 3/8", Grade 5 hardware
- THREADS:
 - Swivel: 1/2" NPT (F x F)
 - Delivery Hose: 1/2" NPT (M x M)
- WARRANTY (*Defects in material and workmanship, non-wear parts*):
 - Five years for hardware
 - One year for hose
- ACCESSORIES:
 - TIM-4218-2N Connecting Hose, 1/2" x 1/2" NPT (M x M), 300 PSI, 2' long
- INSTALLATION RECOMMENDATIONS:
 - Two parallel runs of, Kindorf Strut Channel affixed to steel roofing supports. Four each, 3/8", Grade 5 bolts, flat/lock washers and Kindorf Spring Nuts *per Kindorf pair*
 - Typical mounting bolt specifications: Grade 5, 3/8-16, 1-1/2" (length as required)
 - Keep reel and associated plumbing away from heat sources
 - Plumbing, 1/2" diameter, K-Copper plumbing with copper or brass fittings
 - Three wraps Teflon tape followed by pipe dope



Reel Dimensions In Inches						
Size Index	A	B	C	D	E	Mount L-M
1	9-1/4"	25-1/2"	23"	8"	9"	7" x 8"

