

# Data Sheet, TIM-3208-75P Hose Reel (Platinum Series Premium Double-Arm)

Medium Pressure (2,500 PSI), powder-coated, double-arm reel,  
1/2" x 75' delivery hose

- **HOSE:**
  - Working pressure, 2,500 PSI maximum
- **SHIPPING:**
  - One box
  - *Weight:* 100 pounds
  - *Dimensions:* 9.25" x 25.5" x 23"
- **COMPATIBILITY:**
  - Oil
  - Automatic Transmission Fluid
  - Antifreeze
- **MAXIMUM MOUNTING HEIGHT:**
  - 14' above floor
- **MOUNTING BASE HOLE PATTERN:**
  - 7" x 8"
  - Four holes for 3/8", Grade 5 hardware
- **THREADS:**
  - *Swivel:* 1/2" NPT (F x F)
  - *Delivery Hose:* 1/2" NPT (M x M)
- **WARRANTY (Defects in material and workmanship, non-wear parts):**
  - Five years for hardware
  - One year for hose
- **ACCESSORIES:**
  - TIM-4418-2NS Connecting Hose, 1/2" x 1/2" NPT (M x M), 2,000 PSI, 2' long
- **INSTALLATION RECOMMENDATIONS:**
  - Two parallel runs of, Kindorf Strut Channel affixed to steel roofing supports. Four each, 3/8", Grade 5 bolts, flat/lock washers and Kindorf Spring Nuts *per Kindorf pair*
  - Typical mounting bolt specifications: Grade 5, 3/8-16, 1-1/2" (length as required)
  - Keep reel and associated plumbing away from heat sources
  - Plumbing, 5/8" diameter, seamless steel tubing with steel tubing connectors
  - Three wraps Teflon tape followed by pipe dope



Reel Dimensions In Inches						
Size Index	A	B	C	D	E	Mount L-M
1	9-1/4"	25-1/2"	23"	8"	9"	7" x 8"

