

Data Sheet, TIM-3936-50 Hose Reel (Advantage Plus Series)

High Pressure (4,000 PSI), powder-coated, double-arm reel,
3/8" x 50' delivery hose

- HOSE:
 - Working pressure, 4,000 PSI maximum
- SHIPPING:
 - One box
 - Weight: 83 pounds
 - Dimensions: 20.5" x 23" x 9"
- COMPATIBILITY:
 - Grease
- MAXIMUM MOUNTING HEIGHT:
 - 14' above floor
- MOUNTING BASE HOLE PATTERN:
 - 3.5" x 7.5"
 - Four holes for 3/8", Grade 5 hardware
- THREADS:
 - Swivel: 3/8" NPT (F x F)
 - Delivery Hose: 3/8" NPT (M x M)
- WARRANTY (*Defects in material and workmanship, non-wear parts*):
 - Five years for hardware
 - One year for hose
- ACCESSORIES:
 - TIM-3900-50, Slide-in mounting bracket. Four holes for 3/8", Grade 5 hardware
 - TIM-4516-2N Connecting Hose, 3/8" x 3/8" NPT (M x M), 4000 PSI, 2' long
- INSTALLATION RECOMMENDATIONS:
 - Two parallel runs of, Kindorf Strut Channel affixed to steel roofing supports. Four each, 3/8", Grade 5 bolts, flat/lock washers and Kindorf Spring Nuts *per Kindorf pair*
 - Affix TIM-3900-50 bracket(s) to Kindorf pair. Four each, 3/8", Grade 5 bolts, flat/lock washers and Kindorf Spring Nuts *per bracket*. One foot bracket spacing
 - Typical mounting bolt specifications: Grade 5, 3/8-16, 1-1/2" (length as required)
 - Keep reel and associated plumbing away from heat sources
 - Plumbing, 5/8" diameter, seamless steel tubing with steel tubing connectors
 - Three wraps Teflon tape followed by pipe dope



A	B	C	D	E	Mount L-M
9"	20-1/2"	23"	7-1/2"	9"	3-1/2" x 7-1/2"

