

## Data Sheet, TIM-91X-HF Series Mechanical Preset Meter

- **WORKING PRESSURE:**
  - 0 PSI minimum
  - 1,000 PSI maximum
- **SHIPPING:**
  - One box
  - *Weight:* 5 pounds
  - *Dimensions:* 6" x 12" x 12"
  - *Included:* Swivel with filter screen (1x)
- **COMPATIBILITY:**
  - Automatic Transmission Fluid
  - Gear Oil
  - Hydraulic Oil
  - Motor Oil
  - Synthetic Oil
- **BATCH CAPACITY:**
  - *TIM-910-HF:* 16 quart maximum
  - *TIM-911-HF:* 60 quart maximum
  - *TIM-912-HF:* 60 gallon maximum
- **ACCURACY:**
  - *Preset:* ± 0.3%
  - *Mechanical:* ± 0.65%
- **WORKING FLOW RATE:**
  - 3 GPM
- **THREADS:**
  - *Swivel Inlet:* 1/2"-14 NPT (F). NOTE: Sealant required
  - *Meter Outlet:* 1/2"-14 NPT (F). NOTE: Sealant required
- **WARRANTY (*Defects in material and workmanship, non-wear parts*):**
  - One year from date of purchase
- **ACCESSORIES:**
  - PR-100 or PR-750 pressure relief kit (thermal expansion protection)
  - Swivel guards (rubber; various colors available)
- **INSTALLATION RECOMMENDATIONS:**
  - *Plumbing:* 1/2" diameter. Keep plumbing, etc. away from heat sources
  - *Sealant:* Teflon tape topped with petroleum compatible pipe dope (e.g., Gasoila)



TIM-911-HF  
(Meter batch capacity  
determines item number)